

Series	Type (E, EH, EHP, EM, H, HM, M, P, PM)	Upstroking	Downstroking	Maximum Tonnage	Length (in.)		Shut Height (in.)	Stroke Length (in.)	Open Height (in.)	Throat Depth (in.)	Maximum Speed (IPM)			Offline Programming	Gauges			
					Overall	Between Housings					Rapid Approach	Press Speed	Return Speed		Front	Back	Light Curtain	Network Capable
FOREMOST MACHINERY CORP. Northbrook, IL																		
P	FOREMOST SPS WC67Y 63/2500 Hyd.	H		✓	70	98.4	82.6	14.1	3.9	24.6	9.8	3.1	.31	2.36			✓	✓
P	FOREMOST SPS WC67Y 100/3200 Hyd.	H		✓	110 Tons	126	102	17.7	5.9	17.7	12.5	2.36	.31	2.36			✓	✓
L	Foremost Bantam B212	PM		✓	12	41	24.25	7-13	1.88	8.88-14.88	18	200	200	120			✓	
L	Foremost Bantam B412	PM		✓	12	65	48.25	7-13	1.88	8.88-14.88	18	200	200	120			✓	
L	Foremost Bantam B512	PM		✓	12	77	60.25	7-13	1.88	8.88-14.88	18	200	200	120			✓	
L	Foremost Bantam B224	PM		✓	24	35	24.375	7.5-13.5	2	9.5-15.5	21.5	120	120	78			✓	
L	Foremost Bantam B424	PM		✓	24	59	48.375	7.5-13.5	2	9.5-15.5	21.5	120	120	78			✓	
L	Foremost Bantam B624	PM		✓	24	83	72.375	7.5-13.5	2	9.5-15.5	21.5	120	120	78			✓	
L	Foremost Bantam B824	PM		✓	24	107	96.375	7.5-13.5	2	9.5-15.5	21.5	120	120	78			✓	

H-Hydraulic, PM Pneumatic Mechanical

Here's a conversion chart that converts sheet metal gauge numbers into metal thickness.

26 gauge	24 ga.	22 ga.	20 ga .	18 ga.	16 ga.	14 ga.	13 ga.	12 ga.	11 ga.	10 ga.	9 ga.	8 ga.	7 ga.	6 ga.
.018 inch	.024"	.030"	.036"	.048"	.060"	.075"	.090"	.105"	.120"	.135"	.150"	.164"	.180"	.194"
.46mm	.61mm	.76mm	.91mm	1.2mm	1.5mm	1.9mm	2.3mm	2.7mm	3mm	3.4mm	3.8mm	4mm	4.6mm	4.9mm