

	Model/ Configurat ion	Rated Tonnage	Number of Stations	Maximum Hole Diameter (in.)	Autoindex			Accuracy on 1-in. Centers	Strokes per Minute, Nibbling	Workpiece		Throat Depth (in.)	Table Travel Dimensions X x Y (in.)	Table Speed Motion X, Y, Diagonal (IPM)
					Number of Stations	Maximum Hole Diameter (in.)	Rotation Speed			Maximum Material Thickness (in.)	Max. Weight (lbs.)			
<b>FOREMOST MACHINERY CORP. Northbrook, IL</b>														
P	FOREMOST JFY ET-300 Mech.	33	24, 32	3.5	4	3.5	30	.0039	300	.25	330	49	49 x 98	X = 2,200 Y = 2,200
P	FOREMOST JFY VT 300 50"x100" Hyd.	33	32	3.5	4	3.5	30	.0039	600	.25	330	49	49 x 98	X = 3,346 Y = 3,346
P	FOREMOST JFY VT 300 50"x 157" Hyd.	33	32	3.5	4	3.5	30	.0039	600	.25	528	49	49 x 157	X = 3,346 Y = 3,346
P	FOREMOST JFY VT 300 50"x 197" Hyd.	33	32	3.5	4	3.5	30	.0039	600	.25	660	49	49 x 196	X = 3,346 Y = 3,346
P	FOREMOST JFY VT 300 60"x 157" Hyd.	33	32	3.5	4	3.5	30	.0039	600	.25	462	59	59 x 157	X = 3,346 Y = 3,346
P	FOREMOST JFY RT-300 60" x 197" Hyd.	33	20, 32	3.5	5, 4	3.5	40	0.0039	600	1/4	660	59	60" x 197"	X = 1778 Y = 1778
P	FOREMOST JFY RT-300 50" x 100" Hyd.	33	20, 32	3.5	5, 4	3.5	40	0.0039	600	1/4	330	49	50" x 100"	X = 2,159 Y = 2,159
P	FOREMOST JFY RT-300 50" x 197" Hyd.	33	20, 32	3.5	5, 4	3.5	40	0.0039	600, 800	1/4	660	49	50" x 197"	X = 2,159 Y = 2,159
P	FOREMOST JFY RT-300 50" x 157" Hyd.	33	20, 32	3.5	5, 4	3.5	40	0.0039	600, 800, 1,000	1/4	528	49	50" x 157"	X = 2,438 Y = 2,438