

Technical Specification

Model No.		MPP-520	MPP-620
External Dimension		W900 x L1,200 x H1,500	W900 x L1,450 x H1,500
Weight		850 Kgs	1,100 Kgs
Rated Input Voltage		220V – 3 Phase or 380V – 3 Phase	
Hydraulic Motor		3 HP(2.25KW) / 1set 220V/380V – 6P	5 HP(3.75Kw) / 1set 220V/380V – 6P
Hydraulic Pump		Geared Pump / 1set 8 CC / Revolution	Geared Pump / 1set 8 CC / Revolution
Hydraulic Oil		Int'l Standard / MIH S46, ISO VG46	
Oil Change		Every 7 Years	
Oil Reservoir		40 Liters	
Power Consumption		2.0 Kw	3.5 Kw
Power Pressure		Max. 210 Kgs/ cm ²	Max. 280 Kgs/cm ²
Throat Depth		520 mm	620mm
Max. Capacity	Steel	T3.2 x W1,040	T4.0 x W1,240
	Stainless	T1.8 x W1,040	T2.4 x W1,240
	Aluminum	T10 x W1,040	T15 x W1,240
	Hole	Φ114, 114x114	Φ114, 114x114
<p>< Punching Hole Patterns ></p> <ul style="list-style-type: none"> - Round Hole - Meter Hole - Square Hole - Corner Notching Hole - Push Lock Hole - Lamp Hole - Key Lock Hole - Volt / Ampere Meter Hole - Louver Hole (12x60, 15x80, 15x100, 20x120) - Any other hole patterns according to Customer's order. <p>Any kind of patterns with dimensions are available, but within max. hole capacity.</p>			